

02/16/99

A

Please type a plus sign (+) inside this box ➔ +

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PTO/SB/05 (4/98)  
Approved for use through 09/30/2000. OMB 0651-0032  
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	081862.P137
First Inventor or Application Identifier	David A. Hughes
Title	METHOD FOR IMPLEMENTING AUTOMATIC PROTECTION SWITCHING
Express Mail Label No.	EL123182159US

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

1. ☒ Fee Transmittal Form  
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 22]  
(preferred arrangement set forth below)
- Descriptive title of the Invention
  - Cross References to Related Applications
  - Statement Regarding Fed sponsored R & D
  - Reference to Microfiche Appendix
  - Background of the Invention
  - Brief Summary of the Invention
  - Brief Description of the Drawings (if filed)
  - Detailed Description
  - Claim(s)
  - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 6]
4. Oath or Declaration [Total Pages   ]
- a. ☐ Newly executed (original copy)
- b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))  
(for continuation/divisional with Box 16 completed)
- i. ☐ **DELETION OF INVENTOR(S)**  
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR §§ 1.63(d)(2) and 1.33(b).

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission  
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of Attorney  
(when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO - 1449 ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
13. ☐ \*Small Entity Statement(s) ☐ Statement filed in prior application, Status still proper and desired
14. ☐ Certified Copy of Priority Document(s)  
(if foreign priority is claimed)
15. ☐ Other: .....

**\*NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).**

16. If a **CONTINUING APPLICATION**, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: \_\_\_\_\_

Prior application Information: Examiner \_\_\_\_\_

Group/Art Unit: \_\_\_\_\_

For **CONTINUATION** or **DIVISIONAL APPS** only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

## 17. CORRESPONDENCE ADDRESS

☐ Customer Number of Bar Code Label

(Insert Customer No. or Attach bare code label here)

or ☒ Correspondence address below

Name	BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP				
Address	12400 Wilshire Boulevard, Seventh Floor				
City	Los Angeles	State	California	Zip Code	90025
Country	U.S.A.	Telephone	(714) 557-3800	Fax	(714) 557-3347

Name (Print/Type) Roger W. Blakely, Jr., Reg. No. 25,831

Signature

*Roger W. Blakely, Jr.*

Date

02/16/99

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

UNITED STATES PATENT APPLICATION

FOR

**METHOD FOR IMPLEMENTING AUTOMATIC  
PROTECTION SWITCHING (APS) USING CELL  
REPLICATION**

Inventor: David A. Hughes  
Onchuen D. Lau  
Frank H. Chui  
Quang H. Nguyen

Prepared By:

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP  
12400 Wilshire Blvd., 7th Floor  
Los Angeles, California 90025-1026  
(714) 557-3800

# METHOD FOR IMPLEMENTING AUTOMATIC PROTECTION SWITCHING (APS) USING CELL REPLICATION

## Field of the Invention

The present invention is related to networks. In particular, the  
5 method and apparatus of the present invention relates to Automatic  
Protection Switching (APS) using cell replication.

## Background

Automatic Protection Switching (APS) is a means to provide  
redundancy on Synchronous Optical Network (SONET) equipment to guard  
10 against line failures.

There are three types of linear APS modes, namely, 1+1, 1:1 and 1:n.  
All three modes require that if any failures are detected in a working line, a  
switch to a protection line must be initiated in 10 msec and completed in 50  
msec for a total of 60 msec.

15 In the linear APS 1+1 mode, for every working line, there is a  
corresponding redundant protection line. Traffic is carried by both the  
working and protection lines simultaneously.

In the linear APS 1:1 mode, for every working line, there is a  
corresponding redundant protection line. However, traffic is normally  
20 carried on the working line only. When a failure is detected in the working  
line, traffic is switched to the protection line.

In the linear APS 1:n mode, for every 'n' working lines, there is a  
corresponding redundant protection line. Traffic is normally carried on the

working lines only. When a failure is detected in a working line, traffic is switched to the protection line.

Currently, APS is implemented electrically through a multiplexer (MUX)/buffer combination on a line card. The disadvantages inherent in the current technology are many. For example, the APS ports must be in predefined locations, typically adjacent to each other. Additionally, the current scheme does not work at high speed signal transmissions. More specifically, although repeating signals at low speed is tolerable, the scheme breaks down at high speeds due to impedance mismatch and capacitive loading.

## BRIEF SUMMARY OF THE INVENTION

A method for cell replication in which a request for data transmission and mapping information are received by a crossbar and a scheduler and are sent by one of a plurality of software configurable slot remap registers. The  
5 mapping information is indicative of a destination slot and a backup destination slot to which the data is to be transmitted. The method replicates the data by transmitting the data to the destination slot and to the backup destination slot when the data arrives at an input slot of the crossbar.

Other features and advantages of the invention will be apparent from  
10 the detailed description and drawings provided herein.

## BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example and not limitation in the figures of the accompanying drawings in which like references indicated similar elements in which:

5           Figure 1 is a network diagram with an embodiment of a switch fabric with cell replication.

Figure 2 is a block diagram of an embodiment of a switch fabric.

Figure 3 is an exemplary block diagram of the switch fabric with a crossbar architecture.

10           Figure 4 is a switch plane with an embodiment of an APS cell replication feature.

Figure 5 illustrate exemplary registers.

Figure 6 is a flow chart showing the general steps of APS using cell replication.

## DETAILED DESCRIPTION

A method and apparatus for implementing automatic protection switching using cell replication in a network switch fabric is disclosed. For one embodiment, a switch fabric has a slot that can be “dual-homed” to two slots. For example, if slot X is dual homed to slot X and Y, then any traffic that is destined to X will also go to Y. To avoid programming errors, this feature stipulates that one of the dual-homed slots must be itself. In other words, it is an illegal operation if slot X is dual-homed to Y and Z, where X, Y and Z are different values. For one embodiment, the dual homing feature is implemented through a switch fabric register referenced herein as a slot remap register that is under software control. The software may enable the feature on any slot at any time, disable the feature on any slot at any time and modify the slot numbers at any time.

When slot X is dual-homed to X and Y, a request that goes to either X or Y will be treated as if there is a request going to X and Y. A grant is issued to the requesting slot only if both requests (to X and Y) are granted. This applies to unicast and mulitcast traffic.

There are many intended advantages of the embodiment. For example, it is intended that the embodiment eliminate the predefined locations limitations of prior technology. Further, it is intended that no hardware upgrade be necessary in adding the embodiment as the embodiment is performed through software means.

Figure 1 is a network diagram with an embodiment of a switch fabric with cell replication. A network is a collection of computers, printers, routers, switches and other devices that are able to communicate with each

other over some transmission medium. Nodes in a network refer to an endpoint of a network connection or a junction common to two or more lines in a network. Nodes can be processors, controllers, or workstations. Nodes vary in routing and other functional capabilities and can be interconnected by links, and serve as control points in the network.

One embodiment is for a network switch ("switch") which is a chassis based, modular architecture having circuit boards configured to plug into the chassis. A switch is a device that allows a connection to be established as necessary and terminated when there is no longer a session to support.

In the exemplary network diagram, a network node 100 has a network switch 101 with a switch fabric 102. The switch fabric 102 has an APS cell replication feature 150 with a 1+1 implementation where for every working line, there is a corresponding redundant protection line. Traffic is carried by both the working and the protection line simultaneously. A network node 104 also has a network switch 105 having a switch fabric 106 with an APS cell replication feature with a 1 + 1 implementation. The two intermediate nodes 108 and 110 do not need an APS implementation because they are protected on both sides of the network by the APS cell replication features 150 of nodes 100 and 104.

In an alternate embodiment, the APS cell replication feature can be implemented to protect physical lines between the network nodes.

Figure 2 is a block diagram of one embodiment of a switch fabric. For one embodiment, a network switch 101, has three types of parts, namely a processor card 200, a switch card 202 (switch fabric 102) and a line card 204.

The line card 204 interfaces traffic coming in and out of a physical port with



the switch fabric 102. The interface is accomplished through a switch fabric interface 205 that interfaces the switch fabric 102 with a line card 204 and a layer functions 207 which processes data received from and forwarded to the physical port through framers/transceivers 209<sub>1</sub>...209<sub>N</sub> into an appropriate  
5 format. A processor card 200 is a form of a line card 204 and has the Central Processing Unit (CPU) 203, segmentation and reassembly (SAR) 211 and high level software.

There are a number of switch cards 202 in the system. For one embodiment, there are four switch cards 202. Each switch card 202 has the  
10 APS cell replication feature and has of a number of switch planes 206<sub>1</sub>....206<sub>N</sub>, which are the basic elements of a switch fabric 102. For one embodiment, each switch plane 206 has a crossbar 213 and a scheduler 215. Both the crossbar 213 and the scheduler 215 are discussed in detail in the text accompanying Figures 3 and 4.

15 Between every line card 204 and a switch plane 206 there is a physical connection with one direction of traffic going in to the switch fabric 102 and a direction of traffic going out of the switch fabric 102, resulting in a full duplex connection. For example, given sixteen switch planes, there are sixteen connections between the line card 204 and the switch fabric 102.

20 For one embodiment, the APS cell replication feature is implemented in the switch fabric 102, more specifically through the crossbar 213 and the scheduler 215.

Figure 3 is an exemplary block diagram of the switch fabric with a crossbar architecture. Figure 3 is illustrated with ingress slots 300 and egress  
25 slots 302, which are part of the same line card 204, but logically separate. Once

the traffic arrives at a line card 204, requests for transmission made for the traffic comprised of cells are sent to the switch planes  $206_1 \dots 206_N$  of the switch fabric 102.

5 A switch plane 206 receiving a request determines whether to grant the request or not. If the switch plane 206 determines to grant the request, then in the next time slot the line card 204 submits a cell (also referred to herein as data) and the switch plane 206 switches the destination of the cell to an appropriate alternate destination.

10 There are a number of line cards 204 submitting requests to the switch fabric 102. The switch fabric 102 determines which requests to provide grants to. The traffic is then sent to the switch fabric 102 where the traffic is "switched" or "routed" to the appropriate destination slots.

15 The APS cell replication feature repeats a connection using the switch fabric 102. More specifically, a number of registers, referred to herein as slot remap registers, are programmed into each switch planes  $206_1 \dots 206_N$ , such that when traffic is passed to an egress slot 1 (ES1), the traffic is also copied to an egress slot 2 (ES2) where ES1 (active line) is protected by ES2 (standby line). Thus, unlike the prior technology that repeats connections electrically, the APS cell replication feature repeats the connections logically through software control and there is no limitation on transmission speed. Additionally, since  
20 the APS cell replication feature is controlled logically through software control, a given line can protect "n" or any combination of lines, whereas with prior technology, lines physically next to each other were assigned to each other for APS protection.

Figure 4 is a switch plane with an embodiment of the APS cell replication feature. For one embodiment, a switch plane having the APS cell replication feature may be implemented with a switch ASIC 400. For one embodiment, there are two entities within the switch plane 206, namely a crossbar 213, which includes gates to direct traffic, and a scheduler 215 that controls the crossbar 213.

For one embodiment, the scheduler 215 has N signal inputs  $408_1 \dots 408_N$  and N signal outputs  $410_1 \dots 410_N$  and provides control signals  $406_1 \dots 406_N$  to the crossbar 213. The signal inputs  $408_1 \dots 408_N$  to the scheduler 215 are requests for data transmission through the crossbar 213, and the signal outputs  $410_1 \dots 410_N$  are grants (i.e. acknowledgements to the requests).

The crossbar 213 has N data in signals  $412_1 \dots 412_N$  and N data out signals  $414_1 \dots 414_N$  and is an N by N spatial crossbar that may have N concurrent events such as N data coming in and N data going out. Only data for which a request for transmission is granted by the scheduler 215 is processed through the crossbar 213.

Both the crossbar 213 and the scheduler 215 receive mapping information 422 from software configurable slot remap registers  $416_1 \dots 416_N$ . Mapping information 422 identifies the data out destination slots  $414_1 \dots 414_N$  to which data is to be transmitted through the crossbar 213.

For one embodiment, each of the N slot remap registers  $416_1 \dots 416_N$  corresponds with a sequential one of "data in" signals  $412_1 \dots 412_N$  of the crossbar 213. For example, slot remap register  $416_1$  corresponds to data in signal  $412_1$ .

When a request comes in to, for example, input slot 408<sub>1</sub> of the scheduler 215, the scheduler 215 receives the corresponding mapping information 422 from the slot remap register 416<sub>1</sub>. The scheduler 215 then determines whether the destination slot and the backup destination slot as  
5 identified by the mapping information 422 for input slot 408<sub>1</sub> are valid based on the result of arbitration (i.e., whether the destination slot and the backup destination slot are available). For example, the scheduler 215 may grant requests based on some type of priority scheme whereby a grant with the highest predetermined priority is granted a request first and so on. The form  
10 of arbitration to select which destination slot to grant next may vary and is not limited to a priority scheme based arbitration.

Once validity is confirmed, the scheduler 215 transmits a control signal 406 to the crossbar 213 which indicates that 412<sub>1</sub> is permitted to send a cell to its intended destination slot and the backup destination slot. Additionally, an  
15 acknowledgment 418 is sent back to the source 420 of the request, such as an ingress line card. When the data comes in to the crossbar 213, the crossbar 213 knows which route to take the data by the slot identified by the mapping information 422.

Figure 5 illustrates exemplary slot remap registers. In the illustrated  
20 embodiment, there are fourteen registers with five bits and the most significant bit, bit four, determines whether the corresponding traffic is to go to two slots (i.e., "redundant mode"). The four lower bits determine the identity of the current backup slot (i.e., "remap value"). Each register of the slot remap registers 416<sub>1</sub>...416<sub>N</sub> may correspond with one slot (one-to-one  
25 correspondence with 14 registers and 14 slots). The backup slot is assigned to 1

to N slots. In an alternate embodiment, a backup slot is assigned to one specific slot.

The slot remap registers  $416_1 \dots 416_N$  are software configurable. The setting of the slot remap registers  $416_1 \dots 416_N$  may be changed at any given time, the effect of which will take place the next time count. There are two scenarios for which the slot remap registers  $416_1 \dots 416_N$  may be re-programmed to match slots with a changed backup slot. In one scenario, a system that is non-redundant is to be made redundant. In a second scenario, a system's network topology is changed, for instance, network topology may change as more connections are added to the system and connections are deleted due to an increase in network users. Alternatively, the topology of the user changes and the user may want to reconfigure the APS logic. Thus, there are three options for the APS logic, namely, addition, deletion, or reconfiguration of the backup slots. The slot remap registers  $416_1 \dots 416_N$  may be re-programmed accordingly.

Figure 6 is a flow diagram illustrating the general steps followed by one embodiment. In step 601, a request comes in to the scheduler 215. In step 602, the scheduler 215 receives the corresponding mapping information 422 from the slot remap registers  $416_1 \dots 416_N$ . In step 603, the scheduler 215 then determines whether the slot and the backup slot to grant the request to are valid (i.e., available). If the requests are not valid, then a grant will not be issued to the source of the request. In step 604, once validity is confirmed, the scheduler 215 transmits a control signal 406 to the crossbar 213 that indicates that the slot and the backup slot are available. In step 605, when data arrives at the input slot of the crossbar 213, the crossbar 213 transmits the data to its

destination slot and replicates the data cell by transmitting the data to the duo-homed backup destination slot.

What has been described is a method and apparatus that logically duplicates cells in the switch fabric as opposed to performing the APS  
5 electrically.

In the foregoing specification, the invention has been described with reference to specific exemplary embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in  
10 the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

## CLAIMS

What is claimed:

1           1.     A method for cell replication comprising:  
2           receiving a request for data transmission through a crossbar and a  
3           corresponding mapping information, the mapping information received by  
4           the crossbar and received from one of a plurality of software configurable slot  
5           remap registers, the mapping information indicative of a destination slot and  
6           a backup destination slot to which the data is to be transmitted; and  
7           replicating the data by transmitting the data to the destination slot and  
8           to the backup destination slot when the data arrives at an input slot of the  
9           crossbar.

1           2.     The method of claim 1 further comprising determining whether  
2           the destination slot and the backup destination slot to grant the request are  
3           available, the availability determined by a scheduler.

1           3.     The method of claim 2 further comprising transmitting a control  
2           signal to the crossbar once availability is confirmed, the control signal  
3           transmitted by the scheduler and indicative of the availability of the  
4           destination slot and the backup destination slot.

1           4.     The method of claim 3 further comprising sending an  
2 acknowledgment back to a source of the request.

1           5.     An apparatus for cell replication comprising:  
2 a crossbar to direct data traffic; and  
3 a scheduler coupled to the crossbar, the scheduler comprising a  
4 plurality of signal inputs and a plurality of signal outputs and configured to  
5 provide control signals to the crossbar, the plurality of signal inputs being  
6 requests for data transmission through the crossbar, and the plurality of signal  
7 outputs being grants to the requests, data for which a request for transmission  
8 is granted by the scheduler is replicated and processed through the crossbar to  
9 a destination slot and to a backup destination slot according to software  
10 configurable mapping information.

1           6.     The apparatus of claim 5 wherein the crossbar is further  
2 comprised of a plurality of data in signals and a plurality of data out signals  
3 and is a spatial crossbar.

1           7.     The apparatus of claim 6 further comprising a plurality of slot  
2 remap registers coupled to the crossbar and the scheduler, the plurality of slot  
3 remap registers being software configurable and configured to provide the  
4 mapping information to the crossbar and the scheduler, the mapping



5 information identifies the data out destination slots of the crossbar to which  
6 data is to be transmitted through the crossbar.

1 8. The apparatus of claim 7 wherein each the plurality of slot  
2 remap registers corresponds with one of the plurality of data in signals of the  
3 crossbar.

1 9. The apparatus of claim 8 wherein each the plurality of slot  
2 remap registers corresponds with a sequential one of the plurality of data in  
3 signals of the crossbar.

1 10. The apparatus of claim 8 wherein the scheduler receives  
2 mapping information indicative of the destination slot and the backup  
3 destination slot from the slot remap register when a request comes in to one  
4 of the plurality of input slots.

1 11. The apparatus of claim 10 wherein the scheduler determines  
2 whether the destination slot and the backup destination slot as identified by  
3 the mapping information for the specific input slot are available.

1 12. The apparatus of claim 11 wherein the scheduler transmits a  
2 control signal to the crossbar which indicates that data in slot is permitted to

3 send a cell to its intended the destination slot and the backup destination slot  
4 once the availability is confirmed.

1 13. The apparatus of claim 12 wherein the scheduler sends an  
2 acknowledgment back to a source of the request.

1 14. A network switch system comprising:  
2 a plurality of processor cards comprising a central processing unit and  
3 high level software;  
4 a plurality of switch cards coupled to the plurality of processor cards  
5 and implemented with a cell replication feature, the plurality of switch cards  
6 comprises of a plurality of switch planes; and  
7 a plurality of line cards coupled to the plurality of switch cards, the  
8 plurality of line cards to interface the plurality of switch cards with traffic  
9 coming in and out of a plurality of physical ports.

1 15. The system of claim 14 wherein the cell replication feature  
2 further comprises:  
3 a crossbar to direct data traffic; and  
4 a scheduler coupled to the crossbar, the scheduler comprising a  
5 plurality of signal inputs and a plurality of signal outputs and configured to  
6 provide control signals to the crossbar, the plurality of signal inputs being  
7 requests for data transmission through the crossbar, and the plurality of signal  
8 outputs being grants to the requests, data for which a request for transmission

9 is granted by the scheduler is replicated and processed through the crossbar to  
10 a destination slot and to a backup destination slot according to software  
11 configurable mapping information.

1 16. The system of claim 15 wherein the crossbar is further comprised  
2 of a plurality of data in signals and a plurality of data out signals and is a  
3 spatial crossbar.

1 17. The system of claim 16 further comprising a plurality of slot  
2 remap registers coupled to the crossbar and the scheduler, the plurality of slot  
3 remap registers being software configurable and configured to provide the  
4 crossbar and the scheduler the mapping information which identifies the data  
5 out destination slots of the crossbar to which data is to be transmitted through  
6 the crossbar.

1 18. The system of claim 17 wherein each the plurality of slot remap  
2 registers corresponds with one of the plurality of data in signals of the  
3 crossbar.

1 19. The system of claim 18 wherein each the plurality of slot remap  
2 registers corresponds with a sequential one of the plurality of data in signals  
3 of the crossbar.

1           20.    The system of claim 19 wherein the scheduler receives mapping  
2 information indicative of the destination slot and the backup destination slot  
3 from the slot remap register when a request comes in to one of the plurality  
4 of input slots.

1           21.    The system of claim 20 wherein the scheduler determines  
2 whether the destination slot and the backup destination slot as identified by  
3 the mapping information for the specific input slot are available.

1           22.    The system of claim 21 wherein the scheduler transmits a  
2 control signal to the crossbar which indicates that data in slot is permitted to  
3 send a cell to its intended the destination slot and the backup destination slot  
4 once the availability is confirmed.

1           23.    The system of claim 22 wherein the scheduler sends an  
2 acknowledgment back to a source of the request.

1           24.    An apparatus for cell replication comprising:  
2           mean for directing data traffic; and  
3           means for controlling the means for directing, the means for  
4 controlling coupled to the means for directing comprising a plurality of signal  
5 inputs and a plurality of signal outputs and configured to provide control

6 signals to the means for directing, the plurality of signal inputs being requests  
7 for data transmission through the means for directing, and the plurality of  
8 signal outputs being grants to the requests, data for which a request for  
9 transmission is granted by the means for controlling is replicated and  
10 processed through the means for directing to a destination slot and to a  
11 backup destination slot according to software configurable mapping  
12 information.

1 25. The apparatus of claim 24 wherein the means for directing is  
2 further comprised of a plurality of data in signals and a plurality of data out  
3 signals and is a spatial crossbar.

1 26. The apparatus of claim 25 further comprising a plurality of  
2 means for storing coupled to the means for directing and the means for  
3 controlling, the plurality of means for storing being software configurable and  
4 configured to provide the mapping information to the means for directing  
5 and the means for controlling, the mapping information identifies the data  
6 out destination slots of the means for directing to which data is to be  
7 transmitted through the means for directing.

1 27. The apparatus of claim 26 wherein each the plurality means for  
2 storing corresponds with one of the plurality of data in signals of the means  
3 for directing.

1           28.    The apparatus of claim 27 wherein each the plurality means for  
2 storing corresponds with a sequential one of the plurality of data in signals of  
3 the means for directing.

1           29.    The apparatus of claim 28 wherein the means for controlling  
2 receives mapping information indicative of the destination slot and the  
3 backup destination slot from the means for storing when a request comes in  
4 to one of the plurality of input slots.

1           30.    The apparatus of claim 29 wherein the means for controlling  
2 determines whether the destination slot and the backup destination slot as  
3 identified by the mapping information for the specific input slot are available.

1           31.    The apparatus of claim 30 wherein the means for controlling  
2 transmits a control signal to the means for directing which indicates that data  
3 in slot is permitted to send a cell to its intended the destination slot and the  
4 backup destination slot once the availability is confirmed.

1           32.    The apparatus of claim 31 wherein the means for controlling  
2 sends an acknowledgment back to a source of the request.

[illegible][illegible]




FIG. 1






FIG. 2





FIG. 3

FIG. 4



BIT(S)	DEFINITION	RESET VALUE
4	BIT 4 - SLOT00 REDUNDANT MODE	0
3:0	BIT 3:0 - SLOT00 RE-MAP VALUE	0000

BIT(S)	DEFINITION	RESET VALUE
4	BIT 4 - SLOT01 REDUNDANT MODE	0
3:0	BIT 3:0 - SLOT01 RE-MAP VALUE	0001

BIT(S)	DEFINITION	RESET VALUE
4	BIT 4 - SLOT02 REDUNDANT MODE	0
3:0	BIT 3:0 - SLOT02 RE-MAP VALUE	0010

⋮

BIT(S)	DEFINITION	RESET VALUE
4	BIT 4 - SLOT13 REDUNDANT MODE	0
3:0	BIT 3:0 - SLOT13 RE-MAP VALUE	1101

FIG. 5




FIG. 6